





REMOTE DISPLAY


Allows you to monitor critical conditions of operation and execute fresh water flushes.

A 34

The Aquamiser Plus Series offers programmable settings and remote display capability through an advanced control system. This full-featured affordable solution is ideal for smaller water production needs. With outputs of 250–1800 GPD the Aquamiser Plus Series will provide the safety and controls needed to operate both dependably and efficiently. The Aquamiser Plus is available in framed and modular configurations to be utilized in tight spaces and bulkheads. However, despite its small size, the expansive controls include a fully automatic Fresh Water Flush System for unattended maintenance. Scheduled flushes, once a week or every two weeks, will help maintain and keep your watermaker fresh and ready for your next voyage.

MODEL	GPD/LPD	GPH/LPH	HP	ĸw	VOLTAGE
A216S	250/946	10/39	1.5	1.52	120/220, 50/60 Hz
A516S	500/1892	21/79	1.5	1.52	120/220, 50/60 Hz
A616S	600/2270	25/95	1.5	1.52	120/220, 50/60 Hz
A816S	800/3027	33/126	1.5	1.52	120/220, 50/60 Hz
A1226S	1200/4541	50/189	2.5	2.29	120/220, 50/60 Hz
A1826S	1800/6811	75/284	2.5	2.29	120/220, 50/60 Hz

NOTE: Specifications based on 25°C; 32,500 TDS Feed; and, 820psi at 60 hertz











STANDARD FEATURES:

- Staged starting of motors
- Timed start-up (Prime, Init, Run)
- TDS monitoring of product water
- Automatic diverting of water above 500 PPM
- Programmable Fresh Water Flush for automatic and weekly operation; or, convenient one-touch button for manual operation
- Overpressure protection (HP fault)
- Loss of Prime/Fouled Filter detection (LP fault)

FEATURES WITH REMOTE DISPLAY:

- Remote system control up to 150' away
- Readout of product TDS
- Automatic tank level controls
- Programmable times/set points and display settings

OPTIONAL EQUIPMENT/ACCESSORIES:

- Filter Replacement Kit
- Pocket PPM Meter
- Ultra-Violet Sterilizer

